




HS-300C Technical Data Sheet



Pitch: 45mm
 Minimum Width: 195mm
 Open Area: 52%
 Approved: FDA
 Rod: Ø 5.8mm
 Flight: No
 Side Guard: No
 Curve: Yes



Data

Belt Material	Belt Strength				Temperature		Belt Weight
	Straight		Curve		°C (min.)	°C (max.)	(Kg/M ²)
	Kg/M(BW)	N/M(BW)	Kg/M(BW)	N/M(BW)			
Polypropylene	1870	18700	187	187	1	100	6.4
Polyethylene	1330	13300	133	133	- 60	60	6.9
Acetal	2900	29000	290	290	- 40	80	9.6
Nylon	1870	18700	187	187	1	180	8.8
BW – Belt Width							

Color Table

Polypropylene					Polyethylene					Acetal					Nylon				
W	G	N	DB	B	W	G	N	DB	B	W	G	N	DB	B	W	G	N	DB	B
●	●						●			●				●				●	

W–White, G–Gray, N–Nature, DB–Dark brown, B–Blue

Friction Tables


Belt Material	Friction Wearstrips & Products							
	UHMW	HDPE	Steel	Glass	SUS	Plastic	Cardboard	Aluminum
Polypropylene	0.32	0.24	0.15	0.09	0.13	0.08	0.15	0.25
Polyethylene	0.13	0.11	0.26	0.19	0.31	0.16	0.21	0.41
Acetal	0.11	0.09	0.27	0.16	0.26	0.15	0.19	0.28
Nylon	0.18	0.13	0.25	0.16	0.26	0.16	0.19	0.27

SUS – Stainless Steel

Equivalent type with other Brand

Brand Name	Intralox	UNI	Rexnord	MCC	Habasit	KVP
Series & Type	2200	Flex-swb	1200		2500	610
			7956		3800	


The above content is only for reference.



Conveyor Frame Dimensions

Unit : mm


No. Teeth	A (Min.)	B (Min.)	C (Max.)	D (Min.)	T	T1
8	52.5	70	49	250	15	4.5
12	84.7	102.2	81.2	250		



Sprocket Dimensions




Unit: mm

No. Teeth	PD	S	D	H	K
8	120	38.5/40.5	25.2/38.1	25	6.35X3.17
12	184.5	38.5/40.5	30.5/46.5	24	8X8



- ⌘ The minimum turning radius (inside) is 2.2 times of belt width under all feasible belt Width, 2.5 times of belt width is the most optimal.
- ⌘ The minimum straight run section near driving shaft and idling shaft of Radius belt must be 2 times of the belt width in length.
- ⌘ The minimum straight run section between two turns of opposing direction must be 2 times of the belt width in Length.

Guide Rail & Wear Strips




- ⌘ We have different kinds of guide rail and wear strips for your choice; For more information, please consult our sales team.


Support Mode of Insert Roller

⌘ Accumulation

Multi-Speed



Wear Strips are placed between rollers for accumulation.



Wear Strips are placed under the rollers and the speed of products on the belt will be 2 times of the belt speed.