



HS-3600B Technical Data Sheet



Pitch: 50mm
 Minimum Width: 100mm
 Open Area: 27%
 Approved: FDA
 Rod: Ø 5.8 mm
 Flight: Yes
 Side Guard: No
 Curve: No



Data

Belt Material	Belt Strength		Curve	Temperature		Belt Weight
	Straight			°C (min.)	°C (max.)	(Kg/M ²)
	Kg/M(BW)	N/M(BW)				
Polypropylene	1340	13400	--	1	100	8.0
Polyethylene	1280	12800	--	- 60	60	8.0
Acetal	1770	17700	--	- 40	80	12.0
BW – Belt Width						

Color Table

Polypropylene					Polyethylene					Acetal					Nylon				
W	G	N	DB	B	W	G	N	DB	B	W	G	N	DB	B	W	G	N	DB	B
●	●						●			●				●				●	

W-White, G-Gray, N-Nature, DB-Dark brown, B-Blue

Friction Table


Belt Material	Friction Wear strips & Products							
	UHMW	HDPE	Steel	Glass	SUS	Plastic	Cardboard	Aluminum
Polypropylene	0.32	0.24	0.15	0.09	0.13	0.08	0.15	0.25
Polyethylene	0.13	0.11	0.26	0.19	0.31	0.16	0.21	0.41
Acetal	0.11	0.09	0.27	0.16	0.26	0.15	0.19	0.28
Nylon	0.18	0.13	0.25	0.16	0.26	0.16	0.19	0.27

SUS – Stainless Steel

Equivalent type with other Brand

Brand Name	Intralox	UNI	Rexnord	Scanbelt	Habasit	KVP
Series & Type	--	--	--	S.50-100	--	--


The above content is only for reference.



Conveyor Frame Dimensions

Unit : mm

No. Teeth	A (Min.)	B (Min.)	C (Max.)	D (Min.)	T
8	54.6	72.6	50.6	200	16



Sprocket Dimensions

Unit: mm

No. Teeth	PD	S	D	H	K
8	125.2	40.5	--	33.5	--